

Marine Engines

6 M26.3

4 Stroke diesel engine, direct injection

Bore and stroke	150 x 150 mm
Number of cylinders	6 in line
Total displacement	19,90 litres
Compression ratio	15/1
Engine rotation (ISO 1204 standard)	counterclockwise
Idle speed	650 rpm
Flywheel housing	SAE 1
Flywheel	SAE 14"



Customer benefits

Genuine marine design with simple solutions, routine maintenance front area, engine block inspection hatches

Continuous compact power with reference performances in its category

Global environment care with low exhaust emissions, noise reduction and controlled fuel consumption at any running cycle

Latest safe technology including electronic injection dynamic redundancy, high efficient ball bearing turbocharger, integrated circuits with 0 flexible hoses, and more...

Life cycle cost efficiency with extended MTBO, modular concept reducing number of components and interfaces

Rated power - Fuel consumption

Duty	kW	hp	rpm	Fuel consumption g/kWh	l/h	IMO*	EPA*	CCNR	CE97/68
P1	441	600	1800	197	103	II / III	III	II	IIIA
P2	485	660	1800	207	119	II	-	II	IIIA
P2	515	700	2000	203	124	II / III	III	II	IIIA
P2	551	750	2100	209	137	II / III	III	II	IIIA
P3	599	815	2100	216	154	II / III	III	-	-

*IMO III & EPA IV with SCR System.

	P1	P2	P3
Application	unrestricted continuous	continuous	intermittent
Engine load variations	very little or none	continuous	important
Average engine load factor	80 to 100 %	30 to 80 %	50 %
Annual working time	more than 5000 h	3000 to 5000 h	1000 to 3000 h
Time at full load	unlimited	8 h each 12 h	2 h each 12 h

Power definition

(Standard ISO 3046/1 - 1995 (F))

Reference conditions

Ambient temperature	25 °C / 77 °F
Barometric pressure	100 kPa
Relative humidity	30%R
Raw water temperature	25 °C / 77 °F

Fuel oil

Relative density	0,840 ± 0,005
Lower calorific power	42 700 kJ/kg
Consumption tolerances	0 ± 5%
Inlet limit temperature	35 °C / 95 °F

Our ratings also comply with classification societies maximum temperature definition without power derating.

Ambient temperature	45 °C / 113 °F
Raw water temperature	32 °C / 90 °F



Standard equipment

Cooling system

Two - stage cooling circuit with built - in HT thermostatic valve
 Integrated fresh water expansion tank
 High efficiency tubular heat exchanger
 Gear driven centrifugal fresh water pump
 Self priming raw water pump with bronze impeller

Lubrication system

Full flow lube oil filters duplex type - Centrifugal lube oil purifier
 Fresh water cooled lube oil heat exchanger
 Manual priming and draining pump

Fuel system

Common-rail electronic injection
 High pressure pump with shielded high pressure injection rail and pipes
 Fuel oil filter duplex type
 Water separator

Intake air and exhaust system

Double flow raw water cooled intake air heat exchanger module
 Fresh water cooled exhaust gas manifold
 High efficiency dry turbocharger with ball bearing technology


Electrical system

Voltage: 24V DC insulated
 Electrical starter
 190A battery charger

Optional equipment




Cooling circuit configuration for box/keel cooling
 Application injection map (Eco mode - Comfort - High performance)
 Integral electronic injection ECU dynamic redundancy
 High efficiency air filter with blow-by recycler
 Equipment and factory trial according to Classification Societies

Dimensions and dry weight (mm / kg)






Performance




P1 - 441 kW - 600 hp @1800 rpm






P2 - 485 kW - 660 hp @1800 rpm



P2 - 515 kW - 700 hp @2000 rpm



P2 - 551 kW - 750 hp @2100 rpm



P3 - 599 kW - 815 hp @2100 rpm

